

TORC | TECH

Hydraulic Torque Wrenches

Pressure -Torque Conversion Chart

TW-H

PRESSURE			TORQUE NM		
BAR	80-117 mm	120-17 mm	BAR	80-117 mm	120-17 mm
70	4379	4848	390	24397	27010
80	5005	5541	400	25023	27703
90	5630	6233	410	25648	28395
100	6256	6926	420	26274	29088
110	6881	7618	430	26900	29781
120	7507	8311	440	27525	30473
130	8132	9003	450	28151	31166
140	8758	9696	460	28776	31858
150	9384	10389	470	29402	32551
160	10009	11081	480	30027	33243
170	10635	11774	490	30653	33936
180	11260	12466	500	31279	34629
190	11886	13159	510	31904	35321
200	12511	13851	520	32530	36014
210	13137	14544	530	33155	36706
220	13763	15237	540	33781	37399
230	14388	15929	550	34406	38091
240	15014	16622	560	35032	38784
250	15639	17314	570	35658	39477
260	16265	18007	580	36283	40169
270	16890	18699	590	36909	40862
280	17516	19392	600	37534	41554
290	18142	20085	610	38160	42247
300	18767	20777	620	38785	42939
310	19393	21470	630	39411	43632
320	20018	22162	640	40037	44325
330	20644	22855	650	40662	45017
340	21269	23547	660	41288	45710
350	21895	24240	670	41913	46402
360	22521	24933	680	42539	47095
370	23146	25625	690	43164	47787
380	23772	26318	700	43792	48481



TW-H30430

ISO 9001:2015 DS:TW-H-TC0125-EN

The data in the pressure torque table represent the factory calibration verification values