

TORC | TECH

Hydraulic Torque Wrenches

Pressure -Torque Conversion Chart

TW-H



PRESSURE			TORQUE NM		
BAR	27-65 mm	70-80 mm	BAR	27-65 mm	70-80 mm
70	537	603	390	2992	3360
80	614	689	400	3069	3446
90	690	775	410	3145	3532
100	767	861	420	3222	3618
110	844	948	430	3299	3704
120	921	1034	440	3375	3790
130	997	1120	450	3452	3876
140	1074	1206	460	3529	3963
150	1151	1292	470	3606	4049
160	1227	1378	480	3682	4135
170	1304	1464	490	3759	4221
180	1381	1551	500	3836	4307
190	1458	1637	510	3912	4393
200	1534	1723	520	3989	4479
210	1611	1809	530	4066	4566
220	1688	1895	540	4143	4652
230	1764	1981	550	4219	4738
240	1841	2067	560	4296	4824
250	1918	2154	570	4373	4910
260	1995	2240	580	4449	4996
270	2071	2326	590	4526	5082
280	2148	2412	600	4603	5169
290	2225	2498	610	4680	5255
300	2301	2584	620	4756	5341
310	2378	2670	630	4833	5427
320	2455	2757	640	4910	5513
330	2532	2843	650	4986	5599
340	2608	2929	660	5063	5685
350	2685	3015	670	5140	5772
360	2762	3101	680	5217	5858
370	2838	3187	690	5293	5944
380	2915	3273	700	5372	6037

4
5
H
TW-H

The data in the pressure torque table represent the factory calibration verification values.

www.torc-tech.com info@torc-tech.com

A Brand of Surkon International